



Rek-O-Kut "Imperial" Professional Recorder

Precision Rek-O-Kut disc recorder equipped with the M-12S overhead recording lathe. Unit will accommodate all standard vertical-mounting cutting heads. Supplied with 120-line leadscrew; interchangeable with leadscrews up to 270 lines (see below). Lathe can be hand-cranked for run-in and run-off spiral grooves. Calibrated for critical timing. Model A-160, 16" playback pickup arm accommodates records to 16" in diameter. Supplied complete with new cutting head (Model R-56); frequency response, 50-10,000 cps. Less microphone. Uses standard short-shank cutting needle. For 105-125 v., 60 cycle AC. Shpg. wt., 80 lbs.

95 RZ 742. NET 599.95

MODEL M-12S OVERHEAD RECORDING LATHE. Used in "Imperial" professional recorder listed above. Interchangeable with M-12 mechanism. Less head. Shpg. wt., 20 lbs.

95 RZ 745. NET 150.00

MODEL R-56 CUTTING HEAD. For Model M-12S above. Impedance, 8 ohms. Shpg. wt., 1 lb.

95 RC 746. NET 60.00

MODEL M-12S-210 MICROGROOVE LEADSCREW. For Model M-12S recording lathe. 210 lines per inch. Shpg. wt., 1 lb.

95 R 743. NET 44.95

MODEL M-12S-240 MICROGROOVE LEADSCREW. As above except 240 lines per inch. Shpg. wt., 1 lb.

95 R 744. NET 44.95

MODEL TR-43H DUAL-SPEED RECORDING TURNABLE. Dual speed, 12" aluminum turntable. Plays 33 1/2 and 45 rpm. Tapped for M-12S cutter. With heavy-duty, hysteresis synchronous motor. Includes 78-rpm idler. Less cutter. Shpg. wt., 21 lbs.

91 RZ 749. NET 149.95

G. I. Recorder-Phono Assembly

MODEL GI-RB51-LP. Low-cost recorder-phono assembly for cutting and playing recordings. Easily mounted in cabinet, carrying case, etc. Cuts discs up to 10" in diameter at 160 lines per inch (std. groove). Two speeds (33 1/2 and 78 rpm., or 45 and 78 rpm. using adapter spring included for that purpose). Weighted pickup arm provides proper needle pressure for both standard and microgroove records. Steel turntable is rim-driven by 4-pole motor. Convenient depth of cut adjustment. An ideal unit for replacement of older disc recorders. Size, Base plate 15" W, 11 1/2" D; height, 6 1/2", 2 3/4" above, 3 3/4" below plate. Requires high-gain amplifier or radio with 3 watts or more output. Cutter head must be connected to high impedance source. Supplied complete with crystal cutting head less cutting needle (requires short shank type) and playback styli. For operation from 110-120 volts, 60 cycle AC. Shpg. wt., 17 lbs.

96 RX 106. List. \$56.50. NET 33.90

MODEL GI-RB5-LP WITH MAGNETIC HEAD. Same as Model GI-RB51-LP described above, but with Astatic 10-ohm magnetic cutting head. Shpg. wt., 18 lbs.

96 RZ 703. List. \$58.50. NET 35.10

Astatic Disc Recording Heads and Needles

TYPE X-26 CRYSTAL. High impedance; response to 6000 cps. Includes flange for Wilcox-Gay, Knight and G.I. recorders. Connects to plate of output tube or 60,000 ohms transformer secondary. Approximate drive voltage required: 150 v. (rms), 1 1/4 x 1/4 x 3 3/4". With 24" leads. Shpg. wt., 1 lb.

65 R 125. NET 7.53

TYPE M41-8. MAGNETIC. Impedance, 8 ohms; connects directly to amplifier output. Upper frequency limit, 7000 cps. Drive voltage, 3 v. (rms). Size, 1 1/4 x 1/4 x 3 3/4". 24" leads. Shpg. wt., 1 lb.

65 R 128. NET 7.53

KNIGHT STEEL CUTTING NEEDLES. Short shank. Has .003" tip. Average cutting life, 20 minutes. Quiet cutting for fine recording. Shpg. wt., 3 oz.

65 R 803. Pkgs. of 5. NET 59c

KNIGHT SAPPHIRE CUTTING NEEDLE. Precision-ground and highly polished. Short shank. Has .003" tip. Av. life, 5 hrs. 2 oz.

65 RC 800. NET EACH 3.88

Quality Recording Discs for All Purposes

AUDIODISC PROFESSIONAL RECORDING BLANKS

Smooth-coated on both sides of aluminum base. Red Label discs for highest quality work; Yellow Label for general purpose work in studios and schools; Blue Label for home recording. *Large center hole for 45 rpm recordings.

Stock No.	Size	Label	Base	Wt. Ea.	Std. Pkg.	NET EACH		
						Lbs. Pkg.	Std. Pkg.	Single Lots Std. Pkg.
69 R 085	7"	Red	.050	5 oz.	5	25	.91	.82
69 R 069	8"	Red	.040	5 oz.	5	25	.71	.65
69 R 070	10"	Red	.040	6 oz.	8 1/2	25	1.01	.91
69 R 071	12"	Red	.050	9 oz.	13 1/2	25	1.67	1.50
69 RX 072	16"	Red	.050	1 lb.	25	25	3.01	2.70
69 R 089	8"	Yellow	.040	5 oz.	5	25	.61	.55
69 R 090	10"	Yellow	.040	6 oz.	8 1/2	25	.81	.72
69 R 091	12"	Yellow	.050	9 oz.	13 1/2	25	1.30	1.18
69 RX 092	16"	Yellow	.050	1 lb.	25	25	2.42	2.18
69 R 065	6 1/2"	Blue	.027	3 oz.	6 1/2	50	.32	.29
69 R 066	8"	Blue	.027	4 oz.	7 1/2	50	.46	.41
69 R 067	10"	Blue	.027	5 oz.	10 1/2	50	.66	.59

REEVES SOUNDRAFT RECORDING DISCS

THE BROADCASTER. For critical recording. Finest physical and sound properties. Made with scrupulous care. Double face.

Stock No.	Size	Wt. Ea.	Std. Pkg.	NET EACH		
				Lbs. Std. Pkg.	Single Lots	Std. Pkg.
69 R 260	10"	5 oz.	25	8	1.11	1.00
69 R 261	12"	8 oz.	25	14	1.73	1.56
69 RX 262	16"	16 oz.	25	26	3.17	2.86

THE PLAYBACK. Standard broadcast-quality double-faced discs.

Stock No.	Size	Wt. Ea.	Std. Pkg.	NET EACH		
				Lbs. Std. Pkg.	Single Lots	Std. Pkg.
69 R 263	6 1/2"	3 oz.	25	4	.59	.53
69 R 265	10"	5 oz.	25	8	1.01	.91
69 R 266	12"	8 oz.	25	14	1.67	1.50

THE ADDITION. For recording in the home. Double faced discs.

Stock No.	Size	Wt. Ea.	Std. Pkg.	NET EACH		
				Lbs. Std. Pkg.	Single Lots	Std. Pkg.
69 R 268	6 1/2"	3 oz.	25	4	.52	.47
69 R 270	10"	5 oz.	25	8	.81	.73
69 R 271	12"	8 oz.	25	14	1.30	1.17

SEMI-PROFESSIONAL & HOME-TYPE RECORDING DISCS

For home, semi-professional and school use. Aluminum base (except Paper bond base). Cellulose acetate coated. Red Label is semi-professional grade with excellent sound qualities.

Stock No.	Size	Label	Base	Wt. Ea.	Std. Pkg.	NET EACH		
						Lbs. Std. Pkg.	Single Lots	Std. Pkg.
69 R 109	6 1/2"	Orange	†	3 oz.	6	1/2 lb.	25c	15c
69 R 140	6 1/2"	Red	.021"	3 oz.	5	1/2 lb.	30c	27c
69 R 141	8"	Red	.021"	4 oz.	5	3/4 lb.	40c	36c
69 R 142	10"	Red	.021"	4 oz.	5	1 lb.	60c	54c
69 R 143	12"	Red	.021"	6 oz.	5	2 1/2 lbs.	73c	66c
69 R 195	6 1/2"	Purple	.012"	3 oz.	5	1/2 lb.	23c	21c
69 R 196	8"	Purple	.012"	4 oz.	5	3/4 lb.	33c	30c
69 R 197	10"	Purple	.012"	4 oz.	5	1 lb.	47c	42c

RECORD LABELS. Gummed record labels with spaces for title, artist, date, etc. Shpg. wt., per pkg., 2 oz. 50 per pkg.

65 R 520. 4 or more Pkgs., Ea. 31c NET PER PKG. 35c

Disc Cutting Needles

AUDIOPONTS. High-quality recording needles. *For non-professional and Presto Model K recorders. †For professional recorders. 65 R 960 has 87° included angle; 65 R 961, 70°. All .003" except 65 R 966, .001". Shpg. wt., 2 oz.

Stock No.	Mir's Type	Description	NET EACH
65 R 960*	14	Sapphire, short dural shank	4.85
65 R 967*	20	As above, for microgroove	
65 R 961†	14	Sapphire, long dural shank	
65 R 966†	20	As above, for microgroove	
65 R 962*	202	Sapphire, short brass shank	3.88
65 R 963†	202	Sapphire, long brass shank	
65 R 964*	34	Stellite, short brass shank	1.47
65 R 965†	34	Stellite, long brass shank	