

### Neglex Quad Microphone Cables

Mogami Neglex quad cable is perfect cable for home studios suffering from wiring and grounding problems. Mogami 2534 should also be used where intense RFI interference is a problem. Mogami 2534 provides an improvement in signal to noise of 10-20db over equivalent twisted pair cables. Double conductors quad cables are more effective in canceling noise that can get past even the best of shields and is critical in an environment of high RF and EM interference.

- Conductor insulation is XLPE ( Cross-Linked Polyethylene) which has excellent electrical characteristics and prevents shrink-back during soldering.
- Served (spiral) Bare Copper Shield is superior to foil or braided shields for sound quality and simplifies termination.

Part No. W2534



#### Reference Standard NEGLEX Quad High Definition Microphone Cable

NEGLEX No. W2534 has become popular around the world as the standard for high quality digital and analog recording. The cable has also become popular for use with unbalanced equipment, such as high quality pre-amp, amp inputs and tape decks. **Miniature Quad Superflexible Microphone Cable** Originally designed for BANTAM patch-cords, this cable has become popular where a small diameter Quad mic cable is required.

[Back To Top](#)

#### SPECIFICATIONS

Configuration			
Part No.		W2534	W2893
No. of Conductor		4	4(Quad)
Conductor	Details	20/0.12 OFC	30/0.08 OFC
	Size(mm <sup>2</sup> )	0.226mm <sup>2</sup> (#24 AWG)	0.15mm <sup>2</sup> (#26 AWG)
Insulation	Ov. Dia.(mm)	1.6Ø (0.063")	1.0Ø (0.039")
	Material	XLPE (Cross-Linked Polyethylene)	
Served Shield	Colors	Blue / Clear (Quad)	Black / Red / Blue / Clear
	Approx. Ø	Approx. 64/0.18A	Approx. 73/0.12A
Jacket	Ov. Dia.(mm)	6.0Ø (0.236")	4.8Ø (0.189")
	Material	Flexible PVC	Flexible PVC
Roll Sizes	Colors	10 colours available	5 colours available
		50m (164 Ft) 100m (328 Ft) 200m (656 Ft)	50m (164 Ft) 100m (328 Ft) 200m (656 Ft)
Weight per 200m Roll		11kg	7.5kg


[Back To Top](#)

#### ELECTRICAL & MECHANICAL CHARACTERISTICS

Part No.		W2534	W2893
DC Resistance at 20°C	Inner Cond.	0.083Ω/m(0.025Ω/Ft)	0.13Ω/m(0.040Ω/Ft)
	Shield	0.012Ω/m(0.0037Ω/Ft)	0.025Ω/m(0.0076Ω/Ft)
Capacitance at 1kHz, 20°C (Partial C. Value) See below figure*	K <sub>0</sub>	65pF/m(20pF/Ft)	74pF/m(23pF/Ft)
		13pF/m(4pF/Ft)	11pF/m(3.4pF/Ft)
	K <sub>1</sub>	4pF/m(1.2pF/Ft)	3pF/m(0.9pF/Ft)
		97pF/m(29.6pF/Ft)	131pF/m(40pF/Ft)
	Balanced Quad Connection	Cond.-Cond.	Cond.-Shield.
Inductance between conductors at 1kHz, 20°C	Cond.-Cond.	110pF/m(33.6pF/Ft)	178pF/m(54pF/Ft)
	Cond.-Shield.	0.4μH/m(0.12μH/Ft)	0.5μH/m(0.15μH/Ft)
Electrostatic Noise**		50mV Max.	50mV Max.
Electromagnetic Noise**		0.15mV Max.	0.15mV Max.
Microphonics at 50KΩ Load**		430mV Max.	30mV Max.
Voltage Breakdown		Must withstand at DC 500V/15sec.	
Insulation Resistance		100000 M Ω / * m Min. at DC 125V, 20°C	
Flex Life**		11,000 cycles	28,000 cycles
Tensile Strength		688N	500N
Emigration		Non-emigrant to ABS	Non-emigrant to ABS
Applicable Temperature		-20°C +70°C(-4°F +158°F)	

\*\* Using standard testing methods of Mogami Wire & Cable Corp.

\* Partial Capacitance



[Back To Top](#)